

# EVAC+ MULTI-CONNECTION

## Branch

- Facilitates the connection of sanitary fittings to the downpipe and prevents back-siphoning in sanitary fittings and, therefore, the entry of bad odours.
- Compact part**, which allows space to be saved and economises space in ducts.
- Installation of the part under formwork or recessed, guaranteeing the correct gradient of pipes and water drainage.
- Manufactured with a fireproof composition, **NF Me certificate**.
- Compatible with the EVAC+® system.
- M-F branch: F inlet with elastomeric seal and M outlet for fixing.
- Allows the downpipe with no need to install secondary ventilation, regardless of the height of the building according to the standard UNE EN 12056-2.**
- Supplied with two reduction plugs 50-40, which enable a large number of combinations for wastewater drainage.
- Diameters of the connections indicated on the caps.





- An upper block comprising three female inlets (ø50, ø50 and ø40mm) to connect the necessary accessories according to the needs of the sanitary installation.

- The three inlets of the caps will remain closed as a preperforated area that allows for easy opening.

#### EVAC+® Multi-connection branch

- Two longitudinal ribs ensure entry to prevent pipes from obstructing the decompression chamber. This allows the hydraulic capacity of connections to be fully used.
- Possible connections of the discharge branches to the downpipe at 45°, 67° or 87°.
- Double lip seal ensuring watertightness and expansion.

Range	Code	Reference	ND	NF Me	QB
<b>EVAC+</b>	2135284	IMT-554	100		 -181-1935_V4
<b>EVAC+</b>	2135282	IMV-554	110		<small>Compliant with the Avis Technique n°14.1/13-1935_V4</small>

