



SECURITE FEU - NF Me
TUBES ET RACCORDS PVC
*Reference IMV-554-AR



-181-2309_V1

*Compliant with the Avis Technique
n°14.1/21-2309_V1

AR MULTI-CONNECTION

Branch

- Facilitates the connection of sanitary fittings to the downpipe and prevents back-siphoning in sanitary fittings and, therefore, the entry of bad odours.
- Compact part**, which allows space to be saved and economises space in ducts.
- Installation of the part under formwork or recessed, guaranteeing the correct gradient of pipes and water drainage.
- Manufactured with a fireproof composition, **NF Me certificate**.
- Compatible with the EVAC+® system.
- M-F branch: F inlet with elastomeric seal and M outlet for fixing.
- Allows the downpipe with no need to install secondary ventilation, regardless of the height of the building according to the standard UNE EN 12056-2.**
- Supplied with two reduction plugs 50-40, which enable a large number of combinations for wastewater drainage.
- The AR® Soundproof evacuation system also has a **fire rating of B-s1, d0, the highest that a plastic material can achieve.**



- An upper block comprising three female inlets (ø50, ø50 and ø40mm) to connect the necessary accessories according to the needs of the sanitary installation.
- The three inlets of the caps will remain closed as a preperforated area that allows for easy opening.

AR® Multi-connection branch

- Two longitudinal ribs ensure entry to prevent pipes from obstructing the decompression chamber. This allows the hydraulic capacity of connections to be fully used.
- Diameters of the connections indicated on the caps.
- Possible connections of the discharge branches to the downpipe at 45°, 67° or 87°.
- Double lip seal ensuring watertightness and expansion.

The only acoustic Multi-connection Branch with the Avis Technique

Range	Code	Reference	ND	NF Me	QB
-------	------	-----------	----	-------	----



2135283

IMV-554-AR

110



-181-2309_V1

Compliant with the Avis Technique n°14.1/21.2309_V1

